



QTY	MODEL	BASIC CAPACITY BTU/HR I°TD	C.F.M.	FINS PER INCH	MOTOR DATA			COIL SURF SQ. FT.	APPROX WEIGHT	ROOM TEMP	SUCTION TEMP	MARK
					H.P.	VOLTAGE	PHASE					
1	DTX55-1400 DXA HGC	11620	21500	6	1/2	460/60/3	4450	3250	40°F	32.5°F	Dock	

NOTES

- HOUSING - GALVANIZED SHEET STEEL
- DRAIN PAN - ALUMINUM
- INSULATED COVER - GALVANIZED SHEET STEEL
- COIL CONSTRUCTION - ALL STEEL HOT DIPPED GALVANIZED AFTER FABRICATION
- MOTORS - 1140 R.P.M. T.E.M.V. WITH BUILT IN THERMAL OVERLOAD PROTECTION

WORK TO DIMENSIONS DO NOT SCALE PRINT

TOLERANCES
UNLESS OTHERWISE SPECIFIED FOLLOW.
ING TOLERANCES APPLY
FRACTIONAL ± 1/2
ONE PLACE DEC. (.0) ± _____
TWO PLACE DEC. (.00) ± _____
THREE PLACE DEC. (.000) ± _____
ANGULAR ± _____
TOLERANCES ARE NOT CUMULATIVE.

THIS DRAWING IS THE PROPERTY OF KRACK CORP. AND IS SUBJECT TO RETURN UPON REQUEST. IT IS TO BE USED ONLY FOR THE PURPOSE FOR WHICH IT WAS EXPRESSLY LOANED AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF THE KRACK CORPORATION.

F. V. SEPIA												
ASSY.			PROD.									
TOOL ROOM			CONN.									
FIN. PUNCH			COIL									
SHEET METAL			ENG.									
LOCATION	A	LOCATION	A	NO.	CHANGE DESCRIPTION	DATE	CK'D.					
PRINT DISTRIBUTION						REVISIONS						

MATERIAL AS SPECIFIED			
FINISH AS SPECIFIED	SUPERSEDES	SUPERSEDED BY	
DATE 12 JAN 83	SCALE ✓	NO. REQD.	
DRAWN P.C. KRIEGER	CHECKED ✓	APPROVED	

TITLE			
DIMENSIONAL DATA			
DRAW THRU CEILING UNITS w/ HOT GAS DEFROST			
MOD. DTX 55-DXA-HGCLH			JOB NO. 337844
KRACK CORP.			PART NO. 8323E
			REV. 2